

FICHA TÉCNICA

CLEAN WIZ-9/NC

GENERAL

A heavy duty solvent system for cleaning molds, metals and similar objects. Removes resin residues such as epoxy, phenolics, polyesters, polyurethane, etc. as well as grease, waxes, rubber and release agents. Not for removing semi-permanent release.

USE

Mold Cleaning Agent

COMPOSITION

No Chlorinated solvents or CFC's
No class I or II ODC's

A combination of high potency solvents, all of which are active and penetrating. Has slow evaporation rate.

TYPICAL PROPERTIES:

COLOR:	Clear – Yellow Tinted
SPECIFIC GRAVITY:	0.92 @ 25°C
VISCOSITY:	<15 cps @ 25°C
REFRACTIVE INDEX:	1.480 – 1.500
FLASH POINT:	115°F/ 46°C (C.O.C.)
SHELF LIFE:	Minimum of one year
PACKAGING:	Plastic Containers

APPLICATION INSTRUCTIONS

Use full strength. Do not dilute. Apply with a cotton cloth or stiff natural bristle brush (Rugged Charlie Brush). Allow to stand for several minutes to allow CW-9/NC to penetrate and dissolve residue. To remove heavy wax build-up, use a circular motion with the brush to dislodge and penetrate residue. Wipe off with clean cotton cloth before drying. More than one application may suffice to remove free styrene or protective oils from the surface.

PRECAUTIONS

Wear protective gloves made of butyl rubber. Wash hands frequently and if convenient, use protective hand cream. Washing of hands is recommended since CleanWiz-9/NC may penetrate gloves after extended use. Use goggles and do not smoke until hands are completely clean.

When cleaning RTV or rubber molds, apply CleanWiz-9/NC to the outside of the mold a few times to determine if there is any harmful effect to these materials.