

FICHA TÉCNICA

MELAX-3F/NC

GENERAL

Mold conditioner & Sealer. No Chlorinated solvents.

A liquid mold conditioner and sealer for fiberglass, epoxy and aluminium (for wood and plaster molds, use ICN-100 or UFC-P pastes) mold surfaces. Effectively seals the porous areas of mold surfaces resulting in smoother surfaces on the cured resins and aiding in release effect.

COMPOSITION

A proprietary complex emulsion of organic phosphate esters and cross linked polyolefins in combination with otherwise modified fatty acids. Contains emulsifiers, wetting agents and water.

TYPICAL PROPERTIES

Solids:	10 - 12%
Color:	Off white
Specif Gravity:	0.920 @ 25°C
Viscosity:	3000 - 5000 cps @ 25°C
pH:	8.0 - 10.0
Flash Point:	Non Flammable
Shelf Life:	Minimum of one year

APPLICATION INSTRUCTIONS

Clean mold with CLEAN WIZ. Apply with clean cloth, wiping in two directions. Allow to dry for 5 minutes and hand polish to smooth finish. Repeat whenever mold has been treated with CLEAN WIZ or as indicated by smoothness of mold surface.

* La información contenida en este boletín, a nuestro entender, es verdadera y exacta. No obstante, no garantizamos las recomendaciones o sugerencias dadas en él, ya que las condiciones de empleo quedan fuera de nuestro control.